Maxi & Combi Window Awnings

Retractable drop arm window awning systems

The Maxi and Combi retractable window awning from Sunair® is the ideal solution for complete solar control and privacy in your home or business. The awnings can be lowered to any position to provide as little or as much sunlight as you want. With a traditional awning flair the awning fabric when not in use is rolled up and protected by an optional hood or cassette.

- **Reduced cooling costs.**
- **Filter or block sunlight & glare through window.**
- **Fully retractable, eliminating seasonal storage of awnings.**
- **Can be lowered like a shade to create privacy.**
- **Manual or motorized with remote control available.**
- **Hundreds of fabric colors to choose from.**

**Awnings in normal down position**

Awnings lowered 160° for privacy

Revised 02/15/2023

MAXI Retractable window awning

The Maxi window awning is designed for residential and commercial applications and is typically wider than 10 ft. The system utilizes the same roller tube and front bar as our Lateral Arm systems. The arm is designed with a heavy-duty internal spring system. Manual gear operation is standard while hood and motors are optional.

| Type	Standard Frame Colors	Standard Widths	Standard Projections	Recommended Applications	Recommended Fabrics
Large Drop Arm Window Awning Retractable	9 standard Sunair colors	Through 24'	2'4", 3'4", 4'6", 5'8"	Large Window, Porch, Storefronts	Sunbrella, Tempotest / Para, Sattler, & Recasens

5 year limited frame warranty

MEASURING MAXI AWNINGS:

WIDTH:

The width ordered is the measurement from one end of the bracket to the other end of bracket and should include an extra 6 – 8" on each side of the window for proper coverage. The actual fabric is always 4" less than the awning width ordered (see illustration below), and the optional hood is always 1" longer than the awning width.

PROJECTION:

When measuring the projection of the awning take the view from the window into consideration. When the awning is extended in normal position the view should not be obstructed. The projection of the awning should be equal to half the height of the window. The awning will extend down 160 degrees for more privacy and protection from late afternoon sun. Minimum projection available is 15". **For complete information please read the installation manual.**

COMBI Retractable window awning

The Combi window awning is designed for residential and commercial applications up to 12 ft. wide. The system has a small integrated cassette. The arm is designed with a an internal spring system. Manual gear operation is standard while motors are optional.

Type	Standard Frame Colors	Standard Widths	Standard Projections	Recommended Applications	Recommended Fabrics
Small Drop Arm Window Awning Retractable	9 standard Sunair colors	Through 12'	2' , 2'4", 2'8", 3', and 3'4"	Small Windows And Porch openings,	Sunbrella, Tempotest / Para, Sattler, & Recasens

5 year limited frame warranty

MEASURING COMBI AWNINGS:

The recommended width for Combi is the window plus 6 – 8" on each side of glass for proper coverage. The recommended projection is half the height of the window. The cassette housing is 3 ¼" high. The awnings can easily be mounted on to any type of wall or window casing. If mounting the awning on the casing or right above the window, make sure the window does not interfere with the awning or valance when the window is opened. The Combi comes standard with a manual gear mechanism, but can be fitted with an optional motor (See Somfy motor options and controls).

BENEFITS OF AWNINGS

- Reduces indoor temperatures and energy costs while keeping you cool on your deck or patio.

- Reduce heat gain inside by as much as 77% and reduce sunlight and glare through your window by as much as 94% (see Minnesota energy study).

- A Sunair awning keeps you cool on your patio or deck, but it also minimizes your exposure to the sun's harmful rays.

- A Sunair® retractable awning will increase your outdoor living area comfortably and efficiently at a fraction of the cost of a permanent addition

- Increases the value of your home.

100%

23%

Reduce heat gain by 77%

RECOMMENDED

SKIN CANCER FOUNDATION

RECOMMENDED AS AN EFFECTIVE UV PROTECTANT

FRAME COLORS (STANDARD)

Awnings *

*Note: See each model technical page for available frame colors. Available interior screen colors are different than depicted below (see Interior screens).

|				
WHITE Gloss Ral 9010	**MOCHA** Semi Gloss	**DESERT SAND /** **IVORY Gloss**	**BLACK Gloss** Ral 9005	**BRONZE** Coarse

OPTIONAL

|			
GREY Gloss Ral 7040	**BROWN Gloss**	**TAUPE Gloss**	**GREEN Gloss** Ral 6005

FULL RAL COLOR RANGE / EXTRA COST

NOTE: All these colors except Green Ral 6005 and Desert Sand / Ivory are "super durables" which offer better durability compared with standard polyesters powders.

SUNAIR ®
AWNINGS & SOLAR SCREENS

NOTE: *ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES*

ACRYLIC FABRIC COLLECTION

TEMPOTEST®
ITALIAN PERFORMANCE FABRICS

PARÀ

SUNAIR®
AWNINGS & SOLAR SCREENS

STITCHED WITH Tenara SEWING THREAD GORE

Fabric covers sewn with Tenara thread.

|			
5 Forest Green	7 Moss Green	8 Medium Green	11 Red
12 Yellow	13 Ocean Blue	14 Toast	15 White
24 Black	33 Forest Green / White	35 Red / White	37 Yellow / White
47 Brown / Stone	52 Tan	53 Pale Peach	73 Burgundy

75 Navy Blue	**79 Grey**	**81 True Brown**	**84 Dark Terracotta**
87 Fancy Blue	**101 Elite Toast**	**102 Cappuccino**	**106 Toffee**
107 Textured Dk. Grey	**242 Grey / White**	**426 Terracotta**	**439 Dark Grey / White**
809 Cream / Green	**878 Beige / White Speckled**	**926 Taupe Classic Solid**	**931 Green / Cream Wide**
969 Grey Fancy Stripe	**1101 Beige / Stripe Fancy**	**1120 Brown/ Beige Fancy**	**1150 Rust / Green Multi**
116/15 Medium Blue / White	**1243 Yellow Multi**	**1302 Sage Tweed**	**1330/512 Carbon Stitch**

15/1 Beige	**15/14 Raw**	**15/79 Stone**	**4015/91 Raw Speckled**
407/11 Burgundy Tweed	**407/13 Blue Tweed**	**407/14 Toast Classic Tweed**	**407/16 Moss Classic Tweed**
407/3 Green Classic Tweed	**407/6 Green Tweed**	**407/79 Pepper Grey**	**407/926 Grey Classic Tweed**
4215/15 Textured Tan	**5000/57 Cocoa Stripe**	**5001/1 Green Graduated**	**5001/13 Blue Graduated**
5001/7 Moss Graduated	**5001/73 Burg/Grey Graduated**	**5009/1 Beige / Tan Stripe**	**5009/14 Brown / Tan Stripe**
5011/11 Brick/Natural Fancy	**5011/57 Tan / Brown Fancy**	**5011/7 Tan / Green Fancy**	**5071/7 Natural/Moss Graduated**

5072/86 Brown/Stone Fancy

5118/62 Yellow / White Fancy

5144/14 Pastel/Natural Fancy

5167/11 Red / Grey Fancy

5167/2 Blue / Grey Fancy

5167/5 Green / Grey Fancy

5173/12 Yellow / Grey Stripe

5304/15 Rose / Grey Fancy

5347/58 Grey Wheat Multi

5347/79 Platinum Grey Multi

5348/58 Beige / Wheat Multi

5348/79 Grey / Slate Multi

5349/106 Brown Cream Stripe

5349/930 Beige / Brown Classic

5369 Charcoal / Brown

5370 Beige / Grey

5371/727 Grey / Black Stripe

5374 Smoke / Grey Stripe

5396/78 Green Tweed Stripe

5396/930 Hazelnut Stripe

5396/97 Charcoal Tweed Stripe

5397/97 Grey / Black Graduated

5398/107 Carbon Blue Blend

5398/930 Dune / Brown Striped

5399/107 Drk. Grey Tweed	**5399/15 Lgt. Grey Stripe**	**5399/52 Sesame Tweed Stripe**	**5399/94 Stone / Grey Tweed**
5406/52 Coriander Tweed	**5406/94 Textured / Desert Beige**	**5407/107 Charcoal / Stone Tweed**	**5407/15 Textured Silk Grey**
5407/17 Sky Tweed	**5407/52 Sesame Tweed**	**5407/94 Desert Grey Tweed**	**633/79 Grey/ Black Fancy**
634/51 Grey / Natural Fancy	**634/97 Green / Tan Fancy**	**635/11 Cranberry/Natural F.**	**636/10 Grey / Blue Graduated**
636/12 Yellow Graduated	**636/14 Brown Elite Stripe**	**636/5 Green / Beige Fancy**	**636/84 Terracotta Graduated**
638/5 Green Grey Fancy	**639/99 Tan / Natural Fancy**	**641/10 Blue / Beige Fancy**	**727/15 Textured Med. Grey**

739/701 Sage / Beige Fancy

769/75 Cream / Blue Fancy

782/14 Beige Classic Solid

873/151 Dune Tweed

873/2 Textured Cocoa

939/94 Grey Elite Stripe

940/5 Green Elite Stripe

947/14 Pale / Beige Classic

949/91 Brown Beige Classic

950/24 Grey / Charcoal Classic

951/92 Grey / Navy Classic

967/926 Grey/Charcoal Elite

968/426 Terracotta Cream Fancy

97/84 Plum

986/106 Textured Beige

986/15 Textured Lt. Grey

986/727 Textured Pebble Grey

BINDING

A — Binding or Hem	**E** — Standard
B	**F**
C	**G**
D	**H**

VALANCE STYLES

Note:

"A" style straight valance is available with either binding sewn in at bottom, or bottom hem, without binding. All remaining valance styles must have a binding sewn in at bottom (see binding color chart).

Standard valance styles are listed here. Some styles may vary depending on the pattern and where the stripes fall. If a custom valance is required, include a well-dimensioned sketch with the order as well as instructions on style. Our standard valance is "E", if no valance style is specified, we use "E".

BINDING COLORS

passamaneria per mantovane ¡ einfassband
binding tape ¡ galon ‡ border ¡ ribete

15	15/1	52	14	1481	94	57	54	58	12

73	84	11	20	25	26	55	72	56	62	7	5	8

24	81	97	75	87	10	13	74	77	79	21	71	16	6

Colori e numerazioni sono identici alle tinte unite del Tempotest ¡   Coloris et numèration sont les mimes que les unis du Tempotest
Colours and colour references correspond exactly to the Tempotest plains range ¡   Die Farben bzw. die Farbnummer stimmen mit den Tempotest Uni-Farben ¸berein
Colores y numeraciûn son iguales que los lisos del Tempotest

TEMPOTEST
PARA

Teflon
FABRIC PROTECTOR

SOLIDS · TWEEDS · BLOCK STRIPES · FANCY STRIPES · GRADUATED STRIPES

Code	Name	Code	Name	Code	Name
5	Forest Green	407/14	Toast Classic Tweed	5406/52	Coriander Tweed
7	Moss Green	407/16	Moss Classic Tweed	5406/94	Textured Desert Beige
8	Medium Green	407/3	Green Classic Tweed	5407/107	Charcoal/Stone Tweed
11	Red	407/6	Green Tweed	5407/15	Textured Silk Grey
12	Yellow	407/79	Pepper Grey	5407/17	Sky Tweed
13	Ocean Blue	407/926	Grey Classic Tweed	5407/52	Sesame Tweed
14	Toast	4215/15	Textured Tan	5407/94	Desert Grey Tweed
15	White	5000/57	Cocoa Stripe	633/79	Grey/Black Fancy
24	Black	5001/1	Green Graduated	634/51	Grey/Natural Fancy
33	Forest Green/White	5001/13	Blue Graduated	634/97	Green/Tan Fancy
35	Red/White	5001/7	Moss Graduated	635/11	Cranberry/Natural Fancy
37	Yellow/White	5001/73	Burgundy/Grey Graduated	636/10	Grey/Blue Graduated
47	Brown/Stone	5009/1	Beige/Tan Stripe	636/12	Yellow Graduated
52	Tan	5009/14	Brown/Tan Stripe	636/14	Brown Elite Stripe
53	Pale Peach	5011/11	Brick/Natural Fancy	636/5	Green/Beige Fancy
73	Burgundy	5011/57	Tan/Brown Fancy	636/84	Terracotta Graduated
75	Navy Blue	5011/7	Tan/Green Fancy	638/5	Green/Grey Fancy
79	Grey	5071/7	Natural/Moss Graduated	639/99	Tan/Natural Fancy
81	True Brown	5072/86	Brown/Stone Fancy	641/10	Blue/Beige Fancy
84	Dark Terracotta	5118/62	Yellow/White Fancy	727/15	Textured Medium Grey
87	Fancy Blue	5144/14	Pastel/Natural Fancy	739/701	Sage/Beige Fancy
101	Elite Toast	5167/11	Red/Grey Fancy	769/75	Cream/Blue Fancy
102	Cappuccino	5167/2	Blue/Grey Fancy	782/14	Beige Solid Classic
106	Toffee	5167/5	Green/Grey Fancy	873/151	Dune Tweed
107	Textured Dark Grey	5173/12	Yellow/Grey Stripe	873/2	Textured Cocoa
242	Grey/White	5304/15	Rose/Grey Stripe	939/94	Grey Elite Stripe
426	Terracotta	5347/58	Grey/Wheat Multi	940/5	Green Elite Stripe
439	Dark Grey/White	5347/79	Platinum Grey Multi	947/14	Pale Beige Classic
809	Cream/Green	5348/58	Beige/Wheat Multi	949/91	Brown/Beige Classic
878	Beige/White Speckled	5348/79	Grey/Slate Multi	950/24	Grey/Charcoal Classic
926	Taupe Classic Solid	5349/106	Brown/Cream Stripe	951/92	Grey/Navy Classic
931	Green/Cream Wide	5349/930	Beige/Brown Classic	967/926	Grey/Charcoal Elite
969	Grey Fancy Stripe	5369	Charcoal/Brown	968/426	Terracotta/Cream Fancy
1101	Beige/Stripe Fancy	5370	Beige/Grey	97/84	Plum
1120	Brown/Beige Fancy	5371/727	Grey/Black Stripe	986/106	Textured Beige
1150	Rust/Green Multi	5374	Smoke/Grey Stripe	986/15	Textured Light Grey
116/15	Medium Blue/White	5396/78	Green Tweed Stripe	986/727	Textured Pebble Grey
1243	Yellow Multi	5396/930	Hazelnut Stripe		
1302	Sage Tweed	5396/97	Charcoal Tweed Stripe		
1330/512	Carbon Stitch	5397/97	Grey/Black Graduated		
15/1	Beige	5398/107	Carbon Blue Blend		
15/14	Raw	5398/930	Dune/Brown Stripe		
15/79	Stone	5399/107	Dark Grey Tweed		
4015/91	Raw Speckled	5399/15	Light Grey Stripe		
407/11	Burgundy Tweed	5399/52	Sesame Tweed Stripe		
407/13	Blue Tweed	5399/94	Stone/Grey Tweed		

MOTORIZATION

POWERED by
somfy.

Awnings

Exterior Screens

Pergolas

RTS

somfy.

Roller/Solar Shades

Sunair is proud to offer the full line of Somfy motors and controls for our awnings and screens program SOMFY RTS features motors with an integrated radio receiver that allows you to operate the awning by remote control with a wall mounted or hand held remote or by smart phone device.   With a simple click of your remote, the awning or shade will extend or retract automatically. The manual override Sunea motor is ideal for awnings and the Altus motors is ideal for exterior screens. Each motor can be configured with a cord & plug which can simply be plugged into your patio outlet. They are available in 1.4", 11' ,17', & 23' lengths.   Altus motor cords depend on motor model and is standard either 6' or 10' pigtail cords. Optional Altus plug in cords are available in 10', 18', and 24 ' lengths. Optional screen motor is Maestria with obstacle detection. Add Tahoma smart phone and table interface.

SUNEA™ CMO

Ø .77 inches / 19.5 mm

3.87 inches / 98.3 mm

c**U**us

Sunea quick connect

ALTUS®

Twist & Lock Fast Connector Solution for 500 Series Motors
Available 500 Series Motor cable options Q4 2019

➤ Optional LT50 pigtails :
  • 1.6FT SJTW pigtail with LT50 plug on one end & FC on the other
    • 4 conductor version for Wired motors
    • 3 conductor version for RTS & SDN motors

➤ Optional extensions in various lengths for both 4 & 3 conductor cables.
  • same extensions for all AC motors - Sunea, Dia. 40 & 50 ranges
  • interior & exterior rated
  • simplify our offer and standardize going forward with the possibility to totally eliminate the Anderson connector

SUNEA CORDS*

• Version 4 Conductors (for WT motors – mechanical LSUs)

white = neutral
red = direction 1
black = direction 2
green = ground

FC SJTW (4C) 4.4, 8.4, 16.4, 22.4 feet open leads

9020804 FC SJTW (4C) pigtail at 1.6 feet LT50 plug

• Version 3 Conductors (for RTS & SDN motors – electronics LSUs)

FC SJTW (3C) 1.4, 4.4, 8.4, 10.4, 18, 24 feet 45 NEMA

9020803 FC SJTW (3C) pigtail at 1.6 feet LT50 plug

white = neutral
black = hot
green = ground

FC SJTW (3C) 8.4 feet open leads

*Sunea motor pigtail cord is 18". Optional available plug cord lengths are 1.4', 11', 17', and 23' . These cords come with a molded plug that can be plugged into an outlet.

SOMFY REMOTES:

Telis 1 & 4 RTS
Hand-held Remotes

Situo 1 & 4 hand
held remotes

One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in different colors to suit your style, please inquire.</u>

Telis hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.

Telis 1 Chronis
RTS Timer

DecoFlex WireFree™ RTS
Wall Switches

Telis 1 Patio for
exterior use

Smoove® 1 RTS
Surfact Mount Wall Switch

Telis 16 RTS
Hand-held Remote

AVAILABLE AUTOMATIC SENSORS & CONTROLS

SOLIRIS RTS 24V KIT

Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.

ONDEIS® WIREFREE

Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy® motorized exterior products, including awnings and screens.

Sunis & ThermoSunis
Indoor WireFree™ RTS Sensors

SOMFY MOTOR WIRING

Radio Technology Somfy

POWERED by somfy®

Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

The three (3) wire cords can be wired in parallel and can be ordered with a molded plug to simply plug into an exterior UL approved GFI outlet. The standard four (4) wire cords must be hard wired with a traditional toggle wall switch. <u>Screens can not be ordered with molded plugs on the end.</u>

Optional molded plug is available for "awning" motors only

Type of power cable   RTS plug in capable motor cord

RTS
120V AC / 60Hz
3 conductor cable

white = neutral
black = hot
green = ground

All Somfy Motors are UL and CSA Recognized

- All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714

c**UL**us   **CSA**

Type of power cable   STANDARD Hardwire motor cord

Wired
120V AC / 60Hz
4 conductor cable

white = neutral
red   = direction 1
black = direction 2
green = ground

Hardwired motors with a wall switch

5 year Warranty somfy.

somfy® Building happiness

GROUND
NEUTRAL
Power   LINE

DECORATOR PADDLE TOGGLE SWITCH

BROWN
RED
BLACK

GROUND CONNECTED TO BOX

Dimensions

Center Line of Override Shaft
HEX .275"/7mm or SQUARE .236"/6mm

Sunea® RTS CMO

525A2 CMO	535A2 CMO	550R2 CMO	660
25 Nm	35 Nm	50 Nm	60 Nm (530 in. lbs.)
120V / 60HZ	120V / 60HZ	120V / 60HZ	120V / 60Hz
1.6A	2.1A	2.1A	2.5A
20 rpm	20 rpm	14 rpm	14 rpm

POWERED by somfy®

Dimensions

STAR HEAD

2 mounting holes for self tapping screws. Dia. 5 mm (cat #9670013).
Depth 13 mm spaced 1.89" (48 mm) apart.

LT50 Altus® RTS

506	510	525	535	550
6 Nm	10 Nm	25 Nm	35 Nm	50 Nm
120V / 60HZ	120V / 60HZ	120V / 60HZ	120V / 60HZ	120V / 60HZ
1.1A	1.3A	1.6A	2.1A	2.1A
38 rpm	38 rpm	20 rpm	20 rpm	14 rpm

POWERED by somfy®

SUNAIR® / Simu 50 Nm RTS CMO AWNING MOTOR

We offer a "Sunair/Simu motor with our Sunair® & Sunstar® awning model awnings which is more economical. This motor is a 50 Nm radio RTS motor and is available on the above two models only. Maximum width using this motor is 28 ft. wide. This motor kit includes an 18' plug in cord and a one channel hand held remote. All Somfy remotes and electronic controls are compatible and can be added.

TORQUE	SPEED	POWER	CURRENT
50 Nm	12 rpm	250 W	2,1 A

SIMU 60Nm 660 RTS CMO MOTOR

TORQUE	SPEED	POWER	CURRENT
60 Nm	14 rpm	285 W	2,5 A

This motor is a 60 Nm Manual Overide radio RTS motor. Used on Sunair Model awnings above 28 ft wide. This motor kit includes an 18' plug in cord. Remote is additional and not included in kit. All Somfy remotes and electronic controls are compatible and can be added.

La : Drilling dimensions of tubes
Lb : Adapted motor size inside the tube
Lc : Total motor length with adaptor

COMBI AWNING ONLY: Autosun solar powered motor

INSTALLATION

MOTOR

SOLAR PANEL

BATTERY

Exterior Solar Screen

BATTERY

SOLAR PANEL

MOTOR

Drop Arm Window Awning

simu

The Simu solar powered motor can be utilized with smaller sized exterior solar screens and our small Combi window awnings. The available screen models are the SC2000, SC3000, and SC4000 models with standard track or cables up to 14 ft. wide (Please see your Sunair dealer for options and limitations).   This battery powered motor does not require a hardwiring or an electrician. The motor kit comes with a solar panel and can be ordered optional with a rechargeable battery pack. You must add a hand held remote to operate.

A COMPLETE SOLAR POWERED SYSTEM

SOLAR POWER

AutoSun™ DC Hz motor
- AutoSun™ electric motor, dia. 40mm, 12V
- Compatible with existing Hz transmitters

AutoSun™ battery
- NiMH technology
- Lead-free
- Operating Temperature is -4°F to +158°F
- Separate programming button

AutoSun™ solar panel
- Amorphous Silicon technology
- Works effectively even in overcast conditions

Somfy TaHoma® RTS Smartphone and Tablet Interface

The Somfy TaHoma® gateway and smart phone app provides convenient and customized control of Somfy powered motorized shades, blinds, and other motorized solutions. Control up to 40 RTS (Radio Technology Somfy) channels using the TaHoma app. Multiple TaHoma devices can be joined for multi-zone control.

- North America app, you can remotely activate both Zigbee and RTS products Supports UP/DOWN/MY/STOP commands for motorized shades/blinds .

- Supports incremental control for Tilt motors and lighting Supports ON/OFF commands for control of lighting or other devices powered via the Zigbee Smart Plug Multiple users .

- Remote access Control4® Certified Integration with third-party systems over IP Compatible with Somfy Synergy™ API

TaHoma® RTS

Bond Home / Smartphone and Tablet Interface

<u>Bond Bridge</u> and <u>Bond Bridge Pro</u> works as a bridge between Wi-Fi and your remotes recorded signal allowing you to operate your Sunair shades, awnings, pergolas, ceiling fans, fireplaces and more with the Bond app. Works with Somfy and other motor manufacturers.

Bond Bridge

- Works with Alexa, Google Home, and SmartThings,
- Remote Control via Bond Home app
- Works with iPhone or Android
- No installation needed
- Smart home functionality without breaking the bank

Bond Bridge Pro: *Added features...*

- Ethernet port & PoE technology
- Smart home integrations
- Ceiling and wall mount

OPTIONAL:

- <u>Sidekick for Shades</u>: 5-channel Shade and awning

Remote control from anywhere

Be able to control everything even from outside your home.

BOND REMOTE SWITCH:

Sidekick for Shades/Awnings: 5-channel Shade Keypad


- Wireless flush mount shade remote.
- Communicates directly with the shade.
- 10-year battery life.
- Set up shade limits – no manufacturer remote   required.
- This version of Sidekick does not support Scene   Keypad functionality.
- 10-year battery life.
- Install with or without a workbox (flush mount).
- 5-channel control.
- Set up shade limits – no manufacturer remote   required.

Notes

Note: Sunair® reserves the right to change engineering, specifications and prices without notice.
Images and Illustrations in the catalog may vary from digital and printed manuals.

SUNAIR®
AWNINGS & SOLAR SCREENS

SUNPROOFING AMERICA!

MARYLAND LOCATION	ARIZONA LOCATION
Mailing: P.O. Box 1068	Mailing: Same as Jessup
Shipping: 7785 Rt. 175	Shipping: 3807 West Thomas Rd.
Jessup, MD 20794	Phoenix, AZ 85017

MARYLAND		ARIZONA	
Toll Free	800 - 548 - 0408	Toll Free	877 - 272 - 3920
Phone:	410 - 799 - 1145	Phone:	602 - 272 - 3920
Fax:	410 - 799 - 5584	Fax:	602 - 272 - 3925

www.sunairawnings.com   **info@sunairawnings.com**