

SC4500/4600 MASTERSHADE®

Exterior Rolling Zipper Screen / 5" Cassette


The SC4500 is an exterior rolling zipper shade which can be used for sun and insect control or used with clear vinyl windows for light weather protection. The SC4600 can go wider using the same box to 24' wide but is only available with mesh limited in height to 9' high. The fabric runs inside vertical zippered guide tracks by means of gravity. A specially designed horizontal weighted hem bar keeps the fabric taut. The SC4500/SC4600 box is 5 3/16" deep, and 5 ¼" high. The SC4500 is also ideal for use with some Pergola® model awning systems as side screens to create an enclosure.

Туре	Standard Frame Colors	Standard Widths	Standard Heights	Recommended Applications	Recommended Fabrics
Screen Exterior Retractable	9 standard Sunair colors	Through 20' /24' wide Depending on height and Fabric Type	Through 16' high Depending on width, Fabric & Type <u>SC4600 max</u> <u>Height 9 ft.</u>	Residential and commercial res- taurant porches and lenai	Various Mesh & Ferrari 502 vinyl fabric

- Compact design box screen.
- Zipper retention system for fabric.
- Two sizes of zipper available standard
- Ideal with mesh fabric or vinyl fabric and windows.
- Optional "U" channels available for easy installation on uneven walls and columns.
- Gear or Motorized operation.
- Cassette mounts to ceiling or wall without brackets.




SC4500 Mastershade® Installations











Track with optional "U" channel can be added if mounting between columns. The U channel is typically only used if either top opening or bottom opening between columns is more than the other.

Standard track with zipper and track assembly.






SC4500 SCREEN WITH ZIPPER

SC4500 FEATURES:

SUNAIR BENEFIT


Easy to remove roller tube and install cassette on wall or ceiling	SC3569M metal idler bracket for removing roller assembly. Re-enforced cassette with ridges for using smaller screws to install cassette.	The metal idler bracket makes it easy to remove roller tube and fabric and the cassette can be installed without use of brackets. It is designed to withstand the torque of larger heavy shades.
New Improved hem bar and optional larger zipper	Hem bar with internal weight bar hides the weld seams. Optional two sizes of zippers #2 and larger #3 sizes available.	An internal weight bar will not be exposed to the elements and the weld seam is hidden. The optional larger #3 sized zipper is advantageous for windi- er areas and larger screens.
Internal PVC zipper insert with winglets	The SC4500 "Zipper" insert PVC has soft "winglets" on each side of the zipper channel.	Vinyl winglets on the insert PVC provide tension while offering flexibility to expand and contract for the fabric as the temperature changes.
Easily installation of track to wall or side	The SC4500 track is easily attached to the back wall or side wall using small screws rather than track brackets (Back wall shown).	Eliminating track brackets makes for a faster installation and a cleaner look.
U channel for un-even wall installation	The "U" channel can be added to the standard track.	This "U" channel makes it easier to install the tracks between uneven columns or inserting into columns for new construction.





<u>Width:</u> Determine the desired width. The width of the screen is the measurement outside of track to outside of track and outside of cassette to outside of cassette end caps, as both are flush with each other. <u>The track is 1 13/16</u>" wide on each side (See Figure 1). The cassette mounts without using any brackets right on the wall or ceiling. If you mount the tracks on wood trim that protrudes out from the wall, the back of the cassette will have to be built out as well so that it becomes flush with the back of the tracks. The tracks also install right on the wall or post surface with screws (See sketch on next page).

<u>CEILING MOUNTING BETWEEN PILLARS:</u> If mounting under a patio or ceiling mounting, the height is not adjustable and height is total height of opening. Use gasket or bigger brush to make up difference in height from side to side. If mounting between pillars use the narrowest dimension and deduct 1/8" to ¹/4" at top so cassette fits snug with minimal gaps on sides. If there is a very little difference on the width from top to bottom, you may be able to choose the narrowest and install the tracks right to the column and caulk. If distance is bigger, you should add U channels. <u>If ordering the "U" Channels Sunair, will reduce the width of the fabric and hem bar by ³/₄" to allow for the installation of the U channels with about 3/8" play on each side (see drawing next page). Sunair will not reduce the width of the cassette, only the width of fabric, zipper tracks, and hem bar. If the opening is wider at bottom, add U channels to compensate. If opening is no more than 1/2" narrower at bottom the 3/4" deduction on the fabric as per above for U channels will be sufficient. If opening at bottom is more than 1/2" narrower, add U channels, and direct on order for Sunair to deduct 1" on the fabric instead of 3/4" to compensate for U channels and have room for the screws. Sunair can deduct more on fabric if needed, please indicate on order. Commonly, if difference from top to bottom is very small it is common to order only 1 each U channel instead of two for both sides , with smaller deduction.</u>





WALL SURFACE MOUNTING:

If mounting in front of a window opening, add at least 4" to the width of the opening or glass area to fit the screen. If surface mounting determine the height of the opening or window.

HEIGHT:

The fabric or screen mesh should cover the height of the window. The height of the screen includes the cassette height. To calculate the height of the shade if surface mounting to front wall consider adding the height of the cassette (5 1/4") plus 4" (2" at top and 2" at bottom) to the total height of opening to be covered (see sketches on left). This way, the hem bar is not seen while shade is retracted or lowered. Also watch out for casement windows that will interfere with the hem bar when the shade is retracted (In such a case, mount the top of the cassette 7 $\frac{1}{2}$ " - 8" above the opening window edge). In addition, add 2" at the bottom, so the lowered hem bar goes past the glass edge.





BENEFITS OF SOLAR SCREENS



Screen fully lowered down

- Reduces indoor temperatures and saves energy cooling your space.
- Cuts down on solar glare while retaining your view depending on mesh fabric type and openness factor.
- Cuts down on interior fading of floors, carpets and furniture.
- Can offer complete black out privacy blocking all light.



Screen partially lowered down




Screen partially down showing glare




Screen fully down and no glare

BENEFITS OF SOLAR SCREENS cont:



Solar screens can be installed both on the exterior and interior applications of residential and commercial spaces. The benefit with exterior solar screens is that the fabric blocks the sun before it enters the home or space through the glass. Sometimes it is not feasible to install an exterior screen. In such a case, interior screens offer a good alternative. Interior screens are also more economical.

BENEFITS OF EXTERIOR SOLAR SCREENS:



BENEFITS OF ZIPPER SCREENS WITH MESH



- Creates an instant screened in porch with the ability to revert to a full open porch when desired.
- Zipper fabric retention will keep pesky bugs at bay when using a closed mesh fabric.
- Reduces patio temperatures and keeps your space cooler.
- Cuts down on solar glare while retaining your view depending on mesh fabric type and openness factor.
- Cuts down on interior fading of floors, carpets and furniture.







BENEFITS OF ZIPPER SCREENS WITH WINDOWS



- Great for residential and commercial spaces like restaurants.
- Creates an instant enclosed space by lowering the shades.
- Keeps moderate weather at bay by keeping rain and moderate winds from reaching the space.
- Adding heaters will heat the space and make it usable during cooler months.







FRAME COLORS (STANDARD)

Screens*

*Note: See each model technical page for available frame colors. <u>Available interior screen colors are</u> <u>different than depicted below (see Interior screens).</u>



NOTE: All these colors except Green Ral 6005 and Desert Sand / Ivory are "super durables" which offer better durability compared with standard polyesters powders.



NOTE: ACTUAL FRAME COLOR MAY VARY FROM DIGITAL IMAGES






ACRYLIC FABRIC COLLECTION




Fabric covers sewn with Tenara thread.












Graduated

5398/930 Dune / Browi Striped





Grey

bie

SOLIDS · TWEEDS · BLOCK STRIPES · FANCY STRIPES · GRADUATED STRIPES

5	Forest Green	4
7	Moss Green	4
8	Medium Green	-
11	Red	
12	Yellow	4
13	Ocean Blue	40
14	Toast	42
15	White	50
24	Black	5
33	Forest Green/White	50
35	Red/White	5
37	Yellow/White	50
47	Brown/Stone	5
52	Tan	50
53	Pale Peach	50
73	Burgundy	50
75	Navy Blue	5
79	Grey	5
81	True Brown	50
84	Dark Terracotta	51
87	Fancy Blue	51
101	Elite Toast	51
102	Cappuccino	5
106	Toffee	5
107	Textured Dark Grey	51
242	Grey/White	53
426	Terracotta	53
439	Dark Grey/White	53
809	Cream/Green	53
878	Beige/White Speckled	53
926	Taupe Classic Solid	534
931	Green/Cream Wide	534
969	Grey Fancy Stripe	
1101	Beige/Stripe Fancy	
1120	Brown/Beige Fancy	537
1150	Rust/Green Multi	
116/15	Medium Blue/White	53
1243	Yellow Multi	539
1302	Sage Tweed	53
1330/512	Carbon Stitch	53
15/1	Beige	539
15/14	Raw	539
15/79	Stone	539
4015/91	Raw Speckled	53
407/11	Burgundy Tweed	53
407/13	Blue Tweed	53

407/14	Toast Classic Tweed
407/16	Moss Classic Tweed
407/3	Green Classic Tweed
407/6	Green Tweed
407/79	Pepper Grey
07/926	Grey Classic Tweed
215/15	Textured Tan
5000/57	Cocoa Stripe
5001/1	Green Graduated
5001/13	Blue Graduated
5001/7	Moss Graduated
5001/73	Burgundy/Grey Graduated
5009/1	Beige/Tan Stripe
5009/14	Brown/Tan Stripe
500 <i>5/</i> 14 5011/11	Brick/Natural Fancy
5011/57	Tan/Brown Fancy
	Tan/Green Fancy
5011/7	Natural/Moss Graduated
5071/7	
072/86	Brown/Stone Fancy
5118/62	Yellow/White Fancy
5144/14	Pastel/Natural Fancy
5167/11	Red/Grey Fancy
5167/2	Blue/Grey Fancy
5167/5	Green/Grey Fancy
5173/12	Yellow/Grey Stripe
5304/15	Rose/Grey Stripe
5347/58	Grey/Wheat Multi
5347/79	Platinum Grey Multi
5348/58	Beige/Wheat Multi
5348/79	Grey/Slate Multi
849/106	Brown/Cream Stripe
849/930	Beige/Brown Classic
5369	Charcoal/Brown
5370	Beige/Grey
371/727	Grey/Black Stripe
5374	Smoke/Grey Stripe
5396/78	Green Tweed Stripe
896/930	Hazelnut Stripe
5396/97	Charcoal Tweed Stripe
5397/97	Grey/Black Graduated
898/107	Carbon Blue Blend
898/930	Dune/Brown Stripe
899/107	Dark Grey Tweed
5399/15	Light Grey Stripe
5399/52	Sesame Tweed Stripe
5399/94	Stone/Grey Tweed
	-

5406/52	Coriander Tweed
5406/94	Textured Desert Beige
5407/107	Charcoal/Stone Tweed
5407/15	Textured Silk Grey
5407/17	Sky Tweed
5407/52	Sesame Tweed
5407/94	Desert Grey Tweed
633/79	Grey/Black Fancy
634/51	Grey/Natural Fancy
634/97	Green/Tan Fancy
635/11	Cranberry/Natural Fancy
636/10	Grey/Blue Graduated
636/12	Yellow Graduated
636/14	Brown Elite Stripe
636/5	Green/Beige Fancy
636/84	Terracotta Graduated
638/5	Green/Grey Fancy
639/99	Tan/Natural Fancy
641/10	Blue/Beige Fancy
727/15	Textured Medium Grey
739/701	Sage/Beige Fancy
769/75	Cream/Blue Fancy
782/14	Beige Solid Classic
873/151	Dune Tweed
873/2	Textured Cocoa
939/94	Grey Elite Stripe
940/5	Green Elite Stripe
947/14	Pale Beige Classic
949/91	Brown/Beige Classic
950/24	Grey/Charcoal Classic
951/92	Grey/Navy Classic
967/926	Grey/Charcoal Elite
968/426	Terracotta/Cream Fancy
97/84	Plum
986/106	Textured Beige
986/15	Textured Light Grey
986/727	Textured Pebble Grey
	-






RecScreen 5000P



Specifications

Composition: 15% Polyester, 85% Vinyl Syle: Basket Weave Mesh Weight: 14,75 (oz/yd2) Openness Factor: 5.5 % Fabric Thickness (in): .026 Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 5 years exterior Bacteria and Fungal Resistance: AATCC Test Method 100-2004

300 Charcoal / Charcoal





RecScreen



Specifications

Composition: 18% Polyester, 82% Vinyl Syle: Twill Mesh Weight: 17,8 (oz/yd²) Openness Factor: 3 % Fabric Thickness (in): .78 mm Width: 118" Fire classification: NFPA 701 Test 1, and CA Fire Marshall Title 19, Section 1237.1 Warranty: 10 Year Limited. Visit www.recasensusa.com for full warranty. Bacteria and Fungal Resistance: AATCC Test Method 100-2004


300 Charcoal / Charcoal




001 White / Linen



002 White / Sable



004 White / Pearl Grey



502 Dark Gray / Sable



503 Dark Gray / Charcoal



307Charcoal

/ Bronze





Outdoor Screen Fabric. 42% Fiberglass 58% vinyl

3%, 5%, & 10%

Charcoal/Cocoa

930992 Charcoal/Garnet

901901 Grey/Grey

910902

910988

901910 Grey/Sable 30M687

Charcoal/ Cocoa-Fawn

930961

Sable/Wood

Sable/White

10M127 Sable/Sable-Fog

901930 Grey/Charcoal

30M394 Charcoal/ Charcoal-Navy

930993 Charcoal/Forest

930930 Charcoal/ Charcoal



30M394 | Charcoal/Charcoal-Navy 1% 5%

30M394 | Charcoal/Charcoal-Navy





Outdoor Screen Fabric. 42% Fiberglass 58% vinyl

1% & 5%

Charcoal/ Charcoal-Grey

Charcoal/Charcoal

Charcoal/Garnet






Zipper Screens only





Phifer TuffScreen[®] is backed by a 10-year extended limited warranty.



Specifications

Standard Color: Black

Standard Widths: 36[°] (91.4cm), 48[°] (121.9cm), 60[°] (152.4cm), 72[°] (182.9cm), 84[°] (213.4cm), 96[°] (243.8cm), 108[°] (274.3cm) and 120[°] (304.8cm) **Standard Roll Lengths:** 100[°] (30.48m) in all widths and 50[°] (15.24m) in all widths except 120[°]

Packaging: Individually wrapped in protective paper



Heavy-duty, vinyl-coated polyester insect screening
 Ideal for use in high-traffic areas

Durable – resists damage from pets, tears and punctures
 Excellent choice for patios, porch enclosures, retractable systems, windows and doors



Zipper Screens only





Phifer TuffScreen[®] is backed by a 10-year extended limited warranty.



Specifications

Standard Color: Black

Standard Widths: 36[°] (91.4cm), 48[°] (121.9cm), 60[°] (152.4cm), 72[°] (182.9cm), 84[°] (213.4cm), 96[°] (243.8cm), 108[°] (274.3cm) and 120[°] (304.8cm) Standard Roll Lengths: 100[°] (30.48m) in all widths and 50[°] (15.24m) in all widths except 120[°] Packaging: Individually wrapped in protective paper

Proudly made in the

Heavy-duty, vinyl-coated polyester insect screening Ideal for use in high-traffic areas

Durable – resists damage from pets, tears and punctures
 Excellent choice for patios, porch enclosures, retractable systems, windows and doors

Soltis Horizon 86



14 % Open Screen Mesh

Exterior Screen Fabric

5 year warranty from Ferrari



Exterior Screen Fabric TEXTILE NONO[™]9 BRAND FABRIC 5 % Open Screen Mesh ShadowTexture Granite **Expresso** Texture White Stone Texture Flat Black Bone Tobacco Charcoal

TEXTILENE[®] nano[™] 95 is a durable, yet lightweight synthetic fabric. It is lighter and finer with the same technical qualities as the original TEXTILENE[®]. TEXTILENE[®] nano[™]95 is excellent for exterior use and can reduce energy costs while blocking up to 95% of the sun's harmful rays.



502 PROOF SOLTIS / OPAQUE SATINE FINISH COLORS

The Precontraint 502 fabric from Ferrari also offers excellent dimensional stability with minimal stretching and exceptional dirt resistance thanks to a PVDF topcoat on both sides. The fabric is therefore perfect for use on retractable zipper screens with window film. The fabric is 16.8 oz / sq. yd. with a satin finish. Fabrics are fire retardant / certificate is available upon request.



satin finish 5 year warranty from Ferrari





Sunair is proud to offer the full line of Somfy motors and controls for our awnings and screens program SOMFY RTS features motors with an integrated radio receiver that allows you to operate the awning by remote control with a wall mounted or hand held remote or by smart phone device. With a simple click of your remote, the awning or shade will extend or retract automatically. The manual override Sunea motor is ideal for awnings and the Altus motors is ideal for exterior screens. Each motor can be configured with a cord & plug which can simply be plugged into your patio outlet. They are available in 1.4", 11', 17', & 23' lengths. Altus motor cords depend on motor model and is standard either 6' or 10' pigtail cords. Optional Altus plug in cords are available in 10', 18', and 24 ' lengths. Optional screen motor is Maestria with obstacle detection. Add Tahoma smart phone and table interface.



SOMFY REMOTES:



One (1) through (16) channel hand held or wall mounted remotes are available. <u>Remotes are available in</u> <u>different colors to suit your style,</u>

<u>please inquire.</u>



Telis hand-held remotes offer convenient and simple operation of every type of motorized application. Channels help organize the motorized products that are operated. Single channel remotes can operate one individual product or one group of motorized products. Multiple channel remotes can handle groups of motorized products.



AVAILABLE AUTOMATIC SENSORS & CONTROLS



SOLIRIS RTS 24V KIT Sun & Wind Sensor

The Soliris RTS Sun and Wind Sensor automatically controls your RTS motorized products based on current weather conditions.



ONDEIS® WIREFREE Sun & Rain Sensor

The Rain Sensor is a solar-powered combined rain and sun sensor compatible with Radio Technology Somfy[®] motorized exterior products, including awnings and screens.



Sunis & ThermoSunis Indoor WireFree™ RTS Sensors



SOMFY MOTOR WIRING



The three (3) wire cords can be wired in parallel and can be ordered with a molded plug to simply plug into an exterior UL approved GFI outlet. The standard four (4) wire cords must be hard wired with a traditional toggle wall switch. Screens can not be ordered with molded plugs on the end.



Radio Technology Somfy

Optional molded plug

is available for

"awning" motors only

Radio Technology Somfy® (RTS) allows wireless radio control of motorized applications via the RTS family of controls.

> RTS 120V AC / 60Hz 3 conductor cable


All Somfy Motors are UL and CSA Recognized

 All SOMFY motors are UL Recognized and can be found under the following file numbers:

E60495, E60888, E63714







white = neutral black = hotgreen = ground


Type of power cable STANDARD Hardwire motor cord

Wired 120V AC / 60Hz 4 conductor cable

Type of power cable

white = neutral red = direction 1 black = direction 2 green = ground

RTS plug in capable motor cord








LT50 Altus[®] RTS

Dimensions





506	510	525	535	550
6 Nm	10 Nm	25 Nm	35 Nm	50 Nm
120V / 60HZ				
1.1A	1.3A	1.6A	2.1A	2.1A
38 rpm	38 rpm	20 rpm	20 rpm	14 rpm

MAESTRIA OSTACLE

DETECTION EXTERIOR SCREEN MOTOR



Tel an

The

SOMFY <u>Maestria obstacle detection motor</u> is the recommended motor to be used for all zipper screens. These motors accurately detects obstacles, stopping after meeting an object traveling up or down. Protects carrier products and prevents fabric damage resulting from screen bunching and slipping from the guides. The motor senses and distinguishes between an actual obstacle and wind, even wind gusts, so it doesn't stop unnecessarily, resulting in fewer service calls and end user peace of mind.

Obstacle detection*

POWERED by

Accurately detects obstacles, stopping after meeting an object traveling up or down.

Protects carrier products and prevents fabric damage resulting from screen bunching

and slipping from the guides.

Distinguishes between an actual obstacle and wind, even wind gusts, so it doesn't stop

unnecessarily, resulting in fewer service calls and end user peace of mind.

Back release

Releases the motor brake after detecting the obstacle preventing fabric damage.

Somfy TaHoma[®] RTS Smartphone and Tablet Interface

The Somfy TaHoma[®] gateway and smart phone app provides convenient and customized control of Somfy powered motorized shades, blinds, and other motorized solutions. Control up to 40 RTS (Radio Technology Somfy) channels using the TaHoma app. Multiple TaHoma devices can be joined for multi-zone control.



- North America app, you can remotely activate both Zigbee and RTS products Supports UP/ DOWN/MY/STOP commands for motorized shades/blinds.
- Supports incremental control for Tilt motors and lighting I Supports ON/OFF commands for control of lighting or other devices powered via the Zigbee Smart Plug Multiple users .
- Remote access Control4[®] Certified
 Integration with third-party systems over IP
 Compatible with Somfy Synergy[™] API





TaHoma® RTS

Bond Home / Smartphone and Tablet Interface

Bond Bridge and Bond Bridge Pro works as a bridge between Wi-Fi and your remotes recorded signal allowing you to operate your Sunair shades, awnings, pergolas, ceiling fans, fireplaces and more with the Bond app. Works with Somfy and other motor manufacturers.



Remote control from anywhere

Be able to control everything even from outside your home.

Bond Bridge

- Works with Alexa, Google Home, and SmartThings,
- Remote Control via Bond Home app
- Works with iPhone or Android
- No installation needed
- Smart home functionality without breaking the bank

Bond Bridge Pro: Added features...

- Ethernet port & PoE technology
- Smart home integrations
- Ceiling and wall mount

OPTIONAL:

• <u>Sidekick for Shades</u>: 5-channel Shade and awning

BOND REMOTE SWITCH:

Sidekick for Shades/Awnings: 5-channel Shade Keypad




o bond

- Wireless flush mount shade remote.
- Communicates directly with the shade.
- 10-year battery life.
- Set up shade limits no manufacturer remote required.
- This version of Sidekick does not support Scene Keypad functionality.
- 10-year battery life.
- Install with or without a workbox (flush mount).
- 5-channel control.
- Set up shade limits no manufacturer remote required.

Notes

Note: Sunair[®] reserves the right to change engineering, specifications and prices without notice. Images and Illustrations in the catalog may vary from digital and printed manuals.





SUNPROOFING AMERICA!



MARYLAND LOCATION

Mailing: P.O. Box 1068 Shipping: 7785 Rt. 175 Jessup, MD 20794

Toll Free	800	- 548 -	0408
-----------	-----	---------	------

- Phone: 410 799 1145
- Fax: 410 799 5584

www.sunairawnings.com

ARIZONA LOCATION

Mailing: <u>Same as Jessup</u> Shipping: 3807 West Thomas Rd. Phoenix, AZ 85017

Toll Free	877 - 272 - 3920
Phone:	602 - 272 - 3920
Fax:	602 - 272 - 3925

info@sunairawnings.com