

Quality

Weatherproof

Using solution dyed fiber the Tempotest® fabrics have enduring long lasting colors and an excellent dimensional stability.

Fabric protector

Tempotest® fabrics are subject to a special treatment based on Teflon® that gives very high resistance to the natural build up of dirt and a long lasting water and oil repellency.

U.V. Protection

Tempotest® fabrics give an excellent protection withstanding dangerous U.V. radiation.

Maintenance

Basics

To improve the life of your Tempotest® fabric, roll up the awning in strong wind or rain. Should you be forced to roll up the fabric when is wet, dry the fabric as soon as possible.

Avoid the build up of water pockets on the fabric keeping the fabric tight and with an adequate pitch.

Usual periodic care

Remove dust periodically from the dry fabric using a vacuum cleaner or a medium-soft brush. In case of persistent dirt, rinse with clean water at a maximum temperature of 40°C (110° F) using a neutral detergent (this wash might gradually reduce the surface treatment).

Persistent stains

Use a trichloroethylene blotter or a light dry cleaning product.
Never use aggressive strong chemicals.

Warranty

Tempotest® fabric enjoys a 8 YEARS LIMITED WARRANTY

covering unusual color fading and dimensional stability with normal use and exposure.

Any alteration from external agents, damages due to factors beyond our control, mechanical accidents or fraudulent facts are not covered by limited warranty. The limited warranty provides that Parà will replace only the quantity of damaged fabric.